



**Характеристики (n=1400 об/мин)**

| Модель   | Мощность, кВт | Номинальные параметры |        |      | Тормозной момент, Н·м |
|----------|---------------|-----------------------|--------|------|-----------------------|
|          |               | I <sub>N</sub> , А    | КПД, % | cosφ |                       |
| MB63B4   | 0.18          | 0.58                  | 62     | 0.72 | 1.25                  |
| MB71A4   | 0.25          | 0.79                  | 65     | 0.70 | 2                     |
| MB71B4   | 0.37          | 1.12                  | 66     | 0.72 | 2                     |
| MB80A4   | 0.55          | 1.75                  | 69     | 0.66 | 4                     |
| MB80B4   | 0.75          | 2.2                   | 71     | 0.70 | 4                     |
| MB90S4   | 1.1           | 2.8                   | 75     | 0.78 | 10                    |
| MB90L4   | 1.5           | 3.65                  | 76     | 0.80 | 10                    |
| MB100LA4 | 2.2           | 5.1                   | 79     | 0.82 | 20                    |
| MB100LB4 | 3.0           | 6.8                   | 80     | 0.82 | 20                    |
| MB112M4  | 4.0           | 8.7                   | 82     | 0.83 | 40                    |
| MB132S4  | 5.5           | 11.5                  | 83     | 0.83 | 60                    |
| MB132M4  | 7.5           | 15.5                  | 86     | 0.83 | 60                    |